



PowerWalker VI 2000

Line-Interactive UPS System

2000VA Line-Interactive UPS

2x Schuko & 2x IEC outlets, RJ11/RJ45 Surge Protection

USB & RS-232 Connection for monitoring

Cold start, built-in boost and buck AVR function

Auto restart while AC is recovering



Item-No. 10120014



Product Features

PowerWalker VI 2000 is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- RJ11/RJ45 surge protection
- USB and RS-232 communication port
- Monitoring software included
- LED Display show load status or battery capacity
- Green function for energy saving
- Special design allow technicians on-site battery replacement







-

.....

-

_

-

-

_

-

-



Technical Details

Product Features

Capacity	2000VA/1200W
Input Voltage	220/230/240VAC
Input Voltage	170-280VAC
Range	
Input Frequency	45-65Hz (Auto Sensing)
Output Voltage	220/230/240VAC
Voltage Regulation (Battery Mode)	± 10%
Output Frequency	50Hz or 60Hz
Frequency	
Regulation	± 1Hz
(Battery Mode)	
Output Waveform	Simulated Sine Wave
Battery	
Туре	12V / 9Ah
Quantity	2x
Recharge Time	6h for 90% after complete discharge
Transfer Time	
Typical	4-8ms
LED Indicators	
AC Mode	1 st green LED lighting 2 nd to 5 th green LEDs gradually lighting indicating load level
Battery Mode	1 st green LED flashing 2 nd to 5 th green LEDs gradually lighting indicating battery capacity
Fault	Red LED lighting
Audio Indicators	
Battery Mode	Beep every 10sec
Low Battery	Beep every second
Fault	Continuous Beep
Overload	Beep every 0.5sec
Full Protection	
Discharge	Yes
Short-Circuit	Yes
Overcharge	Yes
Overload	Yes

Connections		
Interface	USB, RS-232	
Outlets	2x Schuko, 2x IEC	
Surge Protection	RJ11/RJ45 (in/out)	
Software & System Requirements		
Software	WinPower	
Operating System	For details visit: www.powerwalker.com/winpower.html	
Other	1x USB or RS-232 port	
Product Details		
Dimensions	405 x 145 x 205 mm	
Colour	Black	
Weight	11.6 kg	
Fan Control	Auto OFF: in LINE mode and if internal voltage >27Vdc ON: in battery mode and AVR mode	
Noise Level	< 45dB	
Model Code	VI 2000	
Environment		
Temperature	0°C – 40°C	
Humidity	0% - 90% (non- condensing)	
Package Content		
Package Content	PowerWalker VI 2000, 2x IEC cable, USB cable, RS-232 cable, manual, Software CD	
Optional Accessories		
SNMP Module	ltem-No. 10120503	
Logistic Data		
Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/SR	
Manual Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/SR	
Dimension/Giftbox	495 x 230 x 295 mm	
Weight/Giftbox	11.9kg	
Pieces/Carton	1pcs	
Pieces/Palette	42pcs	
Item Number	10120014	
EAN	4260074970654	
Warranty	24 Month (except battery)	

Version: EN 30/04/2012 We reserve the right for technical changes and mistakes Use UPS configurator on <u>www.powerwalker.com</u> for detailed backup time information.

PowerWalker is a brand of: BlueWalker GmbH Martin-Buber-Strasse 12 • D-41470 Neuss • Germany

Phone: +49 (0) 2137 / 92 98 73 • Fax: +49 (0) 2137 / 78 73 925 info@bluewalker.eu • www.bluewalker.eu • www.powerwalker.com